

Safety Data Sheet for Paints, Coatings, and Chemical Mixtures

Section 1 - Chemical Product and Company Information

Product Name: No Pain Gel Stain

Date Prepared: 4/22/16

Manufactured by :

Dixie Belle Paint Company
1641 Land O Lakes Blvd
Lutz, FL 33549
813-909-1962

Product Use: HOME USE

Section 2 - Composition/ Information on Ingredients

GHS Ratings:

Flammable liquid	4	Flash point $\geq 60^{\circ}\text{C}$ (140°F) and $\leq 93^{\circ}\text{C}$ (200°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $> \text{ce } 2.3 < 4.0$ or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Aspiration hazard		Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity $> 20.5 \text{ mm}^2/\text{s}$ at 40°C .

GHS Hazards

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
P235	Keep cool
P264	Wash ... thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P261	Use personal protective equipment as required
P321	Specific treatment (see __ on this label)
P331	Do NOT induce vomiting

P362	Take off contaminated clothing and wash before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with soap and water
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: See Section 4 for extinguishing
P403+P235	Store in a well ventilated place. Keep cool

Section 3 - Hazards identification

Chemical Name	CAS number	Weight Concentration %
ALIPHATIC HYDROCARBONES	8052-41-3	
METHYL ETHYL KETOXIME	96-29-7	

Section 4 - First Aid measures

INHALATION – If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation, and call a physician. Administer oxygen if a qualified operator is available.

Flash Point: 65 C (149 F)

LEL:

UEL:

Non hazardous non flammable liquid

EXTINGUISHING MEDIA: Use carbon dioxide (CO₂), "Alcohol" foam, dry chemical, or water spray/water fog extinguishing systems

Section 6- Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor-Ensure cleanup personnel. Wear all appropriate protective equipment (PPE). **including respiratory protection.** Remove all ignition sources. **Keep personnel away from contaminated area.**

Section 7 – Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protection Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use product in a manner which minimizes splashes and/or dust.

Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 f (4 to 35C)

Section 8 - Exposure Controls/ Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ALIPHATIC HYDROCARBONES 8052-41-3	500 ppm TWA; 2900 mg/m ³ TWA	100ppmTWA	NIOSH: 350 mg/m ³ TWA 1800 mg/m ³ Ceiling (15 min)
METHYL ETHYL KETOXIME 96-29-7	Not Established	Not Established	Not Established

ENGINEERING: Ensure good air supply and ventilation are used in preparation/use areas.

Section 9- physical and Chemical Properties

This material typically exhibits the following properties under normal circumstances

Boiling Range 150 to 210 °C	Specific Gravity (SG) 0.862
Density, lb/gal 7.2 lbs/gal	Non-Volatile by Weight 43.5 Percent
Non-Volatile by Volume 31.9 Percent	VOC Percent by Weight 56.5 Percent N/A
VOC Percent by Volume 68.1 Percent	VOCS gram/liter 380.911
VOCS, lb/gal 3.17 lbs/gal	

Section 10 - Stability and Reactivity

Stable
UNSTABLE

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Component Toxicity

96-29-7 METHYLETHYLKETOXIME
Oral LD50: 930 mg/kg (Rat) Dermal LD50: 1,000 - (Rabbit)

Toxicological information; No data found

Eyes Kidneys Central Nervous System Skin Respiratory System

Effects of Overexposure

CAS Number	Description	% Weight	Carcinogen Rating
8052-41-3	Aliphatic Hydrocarbones		Aliphatic Hydrocarbones EU Reach: Present (P)

Section 12 – Ecological Information

Ecological Information: No data found

Component Ecotoxicity

Methyl Ethyl Ketoxime	96 Hr LC50 Pimephales promelas: 777 – 914 mg/L (flow through); 96 Hr LC50 Poecilia reticulata: 760 mg/L (static) 48 Hr EC50 Daphnia magna: 750 mg/L 72 Hr EC50 Desmodesmus subspicatus: 83 mg/L
-----------------------	--

Section 13 – Disposal Considerations

As the US EPA, state and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all of the requirements which effect you. Dispose of the hazardous waste at a properly licensed and permitted sit or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream" Refer to Title 40 of the Code of Federal Regulations, Part 261 (40CFR261). This part of the code identities solid wastes which are subject to regulation under various sections of the codes and which are subject to the notification requirements of Section 3010 of the Resource Conservation Act (RCRA)

Section 14 – Transport Information

This material is classified for transport as follows:

Non-hazardous paint

Section 15 – Regulatory Information

Additional regulatory listings, where applicable

N/A

EU Risk Phrases/Safety Phrases: None

Section 16 – Other Information

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 1
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1
Fire = 1
Reactivity = 0

Date Prepared: 4/22/2016